

**PLEASE READ THE USER GUIDE  
BEFORE OPERATING TESTER**

PHONE: +27 63 378 9745

EMAIL: [ajpmobilebox@gmail.com](mailto:ajpmobilebox@gmail.com)

WEB: [www.petertuneup.co.za](http://www.petertuneup.co.za)

Please download the user guide for your device from our website (link below or scan the QR code).

<https://www.petertuneup.co.za/trailertester.html>

Copy and paste the above link into your computer's or smartphone's internet browser. Click on the download user guide link for your device to start downloading; alternatively, contact us if you want it emailed to you.

- ➔ The person who is going to operate the tester must first read and go through all the pages of the user guide.
- ➔ When first opening the packaging box, insert fuses to activate the tester.
- ➔ Tester is not waterproof; keep it away from water, oil, fuel, and other liquids.
- ➔ Clean your tester with oil-based products like turpentine; never use thinners or any other alcohol-based cleaning products.
- ➔ Do not use fuses rated higher than 7.5 amperes.
- ➔ As explained in the user guide, when there is a short on either the trailer or caravan male socket, the voltmeter reading will rapidly drop on the tester when switching on any of the tester toggle switches. The voltmeter drop is an early indication that there is a major short on the wiring of the electrical tow socket you're testing. To prevent the tester fuse and toggle switches from overheating or blowing, keep an eye on the voltmeter and switch the tester off immediately. Find and diagnose shorts first, then continue testing with the tester.

